



E-2 45° Elbows



Quality System Certificate No. 020
BS EN ISO 9001:1994



APPROVED

For Listing/Approval Details
and Limitations visit our Web Site
www.anvilintl.com or contact an
Anvil®/AnvilStar™ Sales Representative.

E-2 45° ELBOW

| Nominal Size | O.D. | Max Wk. Pressure | Center To End | Approx. Wt. Ea. |
|------------------|-----------------|------------------|---------------|-----------------|
| In./DN(mm) | In./mm | PSI/bar | In./mm | Lbs./kg |
| 1¼ 32 | 1.660 42.2 | 300 20.7 | 1¾ 44 | 0.8 0.30 |
| 1½ 40 | 1.900 48.3 | 300 20.7 | 1¾ 44 | 0.9 0.40 |
| 2 50 | 2.375 60.3 | 300 20.7 | 2 51 | 1.0 0.4 |
| 2½ 65 | 2.875 73.0 | 300 20.7 | 2¼ 57 | 1.8 0.8 |
| 3 O.D. 76.1 | 2.996 76.1 | 300 20.7 | 2¼ 57 | 2.1 1.0 |
| 3 80 | 3.500 88.9 | 300 20.7 | 2½ 64 | 2.5 1.1 |
| 4 100 | 4.500 114.3 | 300 20.7 | 3 76 | 4.7 2.2 |
| 5½ O.D. 139.7 | 5.500 139.7 | 300 20.7 | 3¼ 83 | — — |
| 5 125 | 5.563 141.3 | 300 20.7 | 3¼ 83 | 11.6 5.2 |
| 6½ O.D. 165.1 | 6.500 165.1 | 300 20.7 | 3½ 89 | 8.3 3.8 |
| 6 150 | 6.625 168.3 | 300 20.7 | 3½ 89 | 11.6 5.2 |
| 8 200 | 8.625 219.1 | 300 20.7 | 4¼ 108 | 17.9 8.1 |
| 10 250 | 10.750 273.1 | 300 20.7 | 4¾ 121 | 30.0 13.6 |
| 12 300 | 12.750 323.9 | 300 20.7 | 5¼ 133 | 40.4 18.3 |

MATERIAL SPECIFICATIONS:

CAST FITTINGS:

Ductile Iron ASTM A-536

FINISH:

Rust Inhibiting Orange Paint (Standard) or
Hot Dipped Galvanizing per ASTM A-153 (Optional).
Other available options: Example: RAL3000 or RAL9000 Series