




SK-1 caps are specifically designed for use in Fire Protection applications where economy is a factor. All products are UL & ULC listed as well as FM approved. Maximum working pressure for these products is 300 PSI.



Quality System Certificate No. 020
BS EN ISO 9001:1994



APPROVED

For Listing/Approval Details and Limitations visit our Web Site www.anvilintl.com or contact an Anvil®/AnvilStar™ Sales Representative.

SK-1 GROOVED CAP			
Nominal Size	O.D.	End to End	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
1¼	1.660	7/8	0.3
32	42.2	22	0.1
1½	1.900	7/8	0.4
40	48.3	22	0.2
2	2.375	7/8	0.5
50	60.3	22	0.2
2½	2.875	7/8	0.8
65	73.0	22	0.3
3	3.500	7/8	1.2
80	88.9	22	0.6
4	4.500	1	2.0
100	114.3	25	0.9
6	6.625	1	4.6
150	168.3	25	2.1
8	8.625	1	6.0
200	219.1	25	2.7

Additional sizes available, contact an AnvilStar Representative.

MATERIAL SPECIFICATIONS:

CAST FITTINGS:

Ductile iron conforming to ASTM A-536

COATINGS:

Rust inhibiting paint: Color: ORANGE (standard) or Hot Dipped Zinc Galvanized conforming to ASTM A-153 (optional)
Other available options: Example: RAL3000 or RAL9000 Series