

The ex-celsius foam range of extinguishers offer a B classification for flammable liquid fires in addition to a range of class A ratings. With four different sizes available there is a model for every need.



Features

- Working pressure of 14 bar providing optimum discharge reach
- Custom designed plastic base for maximum durability
- Safe to use on electrical equipment of up to 1000V at a distance of 1m
- Complete with wall bracket



Extinguishing Medium	Foam	Foam	Foam	Foam	-
Capacity	2ltr	3ltr	6ltr	9ltr	-
Model Number	TFCE2	TFCE3	TFCE6	TFCE9	-
Fire Rating	8A 34B	8A 89B	21A 144B	21A 183B	-
Height	310mm	500mm	550mm	610mm	-
Cylinder Diameter	110mm	130mm	160mm	180mm	-
Overall Width					-
Full Weight	3.65kg	5.45kg	9.60kg	13.65kg	-
Discharge Range	> 2m	> 2m	> 4m	> 4m	-
Discharge Duration	19 sec	16 sec	18 sec	29 sec	-
Working Pressure	14 bar	14 bar	14 bar	14 bar	-
Temperature Range	+ 5°C to + 60°C	+ 5°C to + 60°C	+ 5°C to + 60°C	+ 5°C to + 60°C	-
Dielectrically Safe	YES	YES	YES	YES	-