

Pump Initiation Boards



Pump Initiation Boards are manufactured from quality components to customer's individual requirements.

As standard they are mounted on a white coated melamine back-board and include LPC Approved glycerine filled pressure gauges, no-loss connectors and Bailey & Mackey pressure switches (or alternatives depending on customer's specifications). The pipe-work is assembled using galvanised pipe and fittings and all Pump Initiation Boards are hydraulically tested to 16bar prior to despatch (28bar rated boards are available upon request).

Boards built with a "single switch" arrangement comply with BS5306 Part 2, whilst "double switch" pump boards are built to the BS EN12845 standard.

SPECIFICATIONS:

| FPC Part Number | Description | Height | Width | Depth | Weight |
|--------------------------|------------------------------------|--------|--------|-------|--------|
| BOA0991WAY | 1 Way Single Switch | 600mm | 400mm | 175mm | 8kg |
| BOA0992WAY | 2 Way Single Switch | 600mm | 600mm | 175mm | 12kg |
| BOA0993WAY | 3 Way Single Switch | 600mm | 800mm | 175mm | 20kg |
| BOA0994WAY | 4 Way Single Switch | 600mm | 1000mm | 175mm | 25kg |
| BOA0992WAYEN12845 | 2 Way Double Switch EN12845 | 700mm | 800mm | 200mm | 24kg |
| BOA0993WAYEN12845 | 3 Way Double Switch EN12845 | 700mm | 1200mm | 200mm | 37kg |
| BOA0994WAYEN12845 | 4 Way Double Switch EN12845 | 700mm | 1800mm | 200mm | 50kg |



**Fire Protection &
Flow Control Products**

Atkinsons Way, Foxhills Industrial Estate, Scunthorpe,
North Lincolnshire, DN15 8QJ

Tel: 01724 854199 Fax: 01724 854213

E-mail: sales@fireprotectioncentre.com

Web: www.fpcdatacentre.co.uk