

OSY2 Supervisory Switch




Models Available

OSY2	OS&Y Supervisory Switch
OSY2A	OS&Y Supervisory Switch (ULC/Canadian)

Replacement Parts

OSYRK	Replacement Hardware Kit
546-7000	Cover Tamper Switch Kit
S07-66-XX	Tamper Screws for Cover
WFDW	Cover Wrench
HEXW	Replacement Hex Wrench



Product Overview

NEMA 3R rated enclosure

User-friendly mounting bracket fits newer valve yokes

Single side conduit entry does not require right angle fittings

Adjustable length actuator eliminates the need for cutting the shaft

Accommodates up to 12 AWG wire

Three position switch monitors vandal and valve close signals

Two SPDT contacts are enclosed in a durable terminal block for added strength

100% synchronization activates both alarm panel and local bell simultaneously

System Sensor's OSY2 is used to monitor the open position of an Outside Screw and Yoke (OS&Y) type gate valve.

Robust Construction. The OSY2 consists of a rugged housing, intended for indoor and outdoor use. When installed with the actuator in the vertical position, the OSY2 is NEMA 3R rated per UL.

Application Flexibility. The OSY2 features a user-friendly mounting bracket and adjustable shaft to permit mounting to most OS&Y valves, ranging in size from 1" to 12". Its right angle design and wide bracket span provides maximum clearance for valve components, to accommodate troublesome valves. Removing the OSY2's gate valve bracket allows the unit to monitor side-bracket style pressure reducing valves.

Simplified Operation. Installation is made easier with the OSY2's single side conduit entrance. By providing a direct conduit pathway to the electrical source, right angle fittings are not required. Installation is further simplified by the OSY2's adjustable length actuator, which eliminates the need for cutting the shaft.

Reliable Performance. The OSY2 is equipped with tamper resistant cover screws to prevent unauthorized entry. Inside, two sets of SPDT (Form C) synchronized switches are enclosed in a durable terminal block to assure reliable performance.



Engineering Specifications

Model shall be model number OSY2 supervisory switch as manufactured by System Sensor. OSY2 shall be installed on each valve as designated on the drawings and/or as specified herein. Switches shall be mounted so as not to interfere with the normal operation of the valve and shall be adjusted to operate within two revolutions of the valve control or when the stem has moved no more than one-fifth of the distance from its normal position. The mechanism shall be contained in a weatherproof die cast metal housing, which shall provide a side entrance for 1/2" conduit and incorporate the necessary facilities for attachment to the valve. A grounding provision is provided. The switch assembly shall include two switches each with a rated capacity of 10 Amp @ 125/250VAC and 2.5 Amp @ 24VDC. The cover shall contain tamper-resistant screws for which a security wrench will be provided with each switch. The OSY2 shall be Underwriters Laboratories listed for indoor or outdoor use. The OSY2 shall be Factory Mutual, CSFM, and MEA approved.

Standard Specifications

Contact Ratings

Two sets of SPDT (Form C)
10.0 A @ 125/250V AC
2.5 @ 6/12/24V DC

Overall Switch Dimensions

5³/₄"H x 3¹/₂"W x 3¹/₄"D
(14.6cm x 8.9cm x 8.2cm)

Bracket Span

2¹/₄"H x 6³/₄"W x 1"D
(5.7cm x 17.1cm x 2.5cm)

Maximum Stem Extension

2⁵/₈" (6.7 cm)

Shipping Weight

2.8 lbs. (1.3 kg)

Conduit Entrances

One single side open for 1/2" conduit

Operating Temperature Range

32°F to 120°F (0°C to 49°C)
Note: The OSY2 will operate from -40°F to 120°F (-40°C to 49°C); however UL does not test control valve supervisory switches below 32°F (0°C).

Enclosure Rating

UL indoor/outdoor
NEMA 3R when mounted with the actuator vertical

Cover Tamper Switch

Standard with ULC model
Optional for UL model, part no. 546-7000

Service Use

Automatic Sprinkler: NFPA 13
One or Two Family Dwelling: NFPA 13D
Residential Occupancies up to 4 stories: NFPA 13R
National Fire Alarm code: NFPA 72


Warranty

3 years


U.S. Patent Nos.

5,478,038; 5,213,205

Electrical Connections for OSY2



OSY2 Mounting



Ordering Information

Model Number	Description
OSY2	Outside Screw and Yoke valve supervisory switch
OSY2A	Outside Screw and Yoke valve supervisory switch (ULC model)

Part Number	Description
OSYRK	Replacement hardware kit (wrenches, screw pack and J-hooks)
546-7000	Cover tamper switch kit
S07-66-XX	Tamper screws for cover
WFDW	Replacement tamper proof wrench for cover
HEXW	Replacement hex wrench

System Sensor Sales and Service

System Sensor Headquarters
3825 Ohio Avenue
St. Charles, IL 60174
Ph: 800-SENSOR2
Fx: 630/377-6495
Documents On Demand:
1-800-736-7672 x3
Web: www.systemsensor.com

System Sensor in Canada
Ph: 905.812.0767
Fx: 905.812.0771

System Sensor in Europe
Ph: + 44.1403.276500
Fx: + 44.1403.276501

System Sensor in China
Ph: + 86.29.524.6253
Fx: + 86.29.524.6259

System Sensor in Singapore
Ph: + 65.273.2230
Fx: + 65.273.2610

System Sensor in the Far East
Ph: + 852.21919003
Fx: + 852.27366580

System Sensor in Australia
Ph: + 613.54.281.142
Fx: + 613.54.281.172

System Sensor in India
Ph: + 91.11.558.2119
Fx: + 91.11.567.6815

PIBV2 Supervisory Switch



Models Available

PIBV2	Post Indicator/Butterfly Valve Supervisory Switch
PIBV2A	Post Indicator/Butterfly Valve Supervisory Switch (ULC/Canadian)

Replacement Parts

A3010-00	Replacement Hardware Kit
546-7000	Cover Tamper Switch Kit
S07-66-XX	Tamper Screws for Cover
WFDW	Cover Wrench
HEXW	Replacement Hex Wrench



Product Overview

NEMA 3R rated enclosure

Bi-directional actuator accommodates rising or falling flags

Single side conduit entry does not require right angle fittings

Adjustable length actuator eliminates the need for cutting the shaft

Accommodates up to 12 AWG wire

Two SPDT contacts are enclosed in a durable terminal block for added strength

100% synchronization activates both alarm panel and local bell simultaneously


System Sensor's PIBV2 supervisory switch monitors the open position of post indicator and butterfly control valves.

Robust Construction. The PIBV2 consists of a rugged housing, intended for indoor and outdoor use. When installed with the actuator in the vertical position, the PIBV2 is NEMA 3R rated per UL.

Application Flexibility. The PIBV2 features a flexible design that accommodates post indicator, butterfly, and many other types of wall post, recessed wall post and pressure reducing valves. The PIBV2's unique bi-directional actuator allows the unit to be installed in either rising or falling flag installations.

Simplified Operation. Installation is made easier with the PIBV2's single side conduit entrance. By providing a direct conduit pathway to the electrical source, right angle fittings are not required. Installation is further simplified by the PIBV2's adjustable length actuator, which eliminates the need for cutting the shaft.

Reliable Performance. The PIBV2 is equipped with tamper resistant cover screws to prevent unauthorized entry. Inside, two sets of SPDT (Form C) synchronized switches are enclosed in a durable terminal block to assure reliable performance.



Engineering Specifications

Model shall be model number PIBV2 Post Indicator Butterfly Valve supervisory switch as manufactured by System Sensor. PIBV2 shall be installed on each valve as designated on the drawings and/or as specified herein. Switches shall be mounted so as not to interfere with the normal operation of the valve and shall be adjusted to operate within two revolutions of the valve control or when the valve flag has moved no more than one-fifth of the distance from its normal position. The mechanism shall be contained in a weatherproof die cast metal housing, which shall provide a side entrance for 1/2" conduit and incorporate a 1/2" NPT nipple for attachment to the valve body. A grounding provision is provided. The switch assembly shall include two switches each with a rated capacity of 10 Amp @ 125/250V AC and 2.5 Amp @ 24V DC. The cover shall contain tamper-resistant screws for which a security wrench will be provided with each switch. PIBV2 shall be Underwriters Laboratories listed for indoor or outdoor use. The PIBV2 shall be Factory Mutual, CSFM, and MEA approved.

Standard Specifications

Contact Ratings

Two sets of SPDT (Form C)
10.0 A @ 125/250V AC
2.5 @ 6/12/24V DC

Overall Switch Dimensions

4 1/4" H x 3 1/2" W x 3 1/4" D
(10.8cm x 8.9cm x 8.2cm)

Maximum Stem Extension

2 1/8" (5.4 cm)

Mounting

1/2" NPT nipple

Conduit Entrances

One single side open for 1/2" conduit

Operating Temperature Range

32°F to 120°F (0°C to 49°C)
Note: The PIBV2 will operate from -40°F to 120°F (-40°C to 49°C); however UL does not test control valve supervisory switches below 32°F (0°C).

Enclosure Rating

UL indoor/outdoor
NEMA 3R when mounted with the actuator vertical

Cover Tamper Switch

Standard with ULC model
Optional for UL model, part no. 546-7000

Shipping Weight

2 lbs. (0.9 kg)

Service Use

Automatic Sprinkler: NFPA 13
One or Two Family Dwelling: NFPA 13D
Residential Occupancies up to 4 stories: NFPA 13R
National Fire Alarm code: NFPA 72


Warranty

3 years


U.S. Patent No.

5,213,205

PIBV2 Mounting



Electrical Connections for PIBV2



Ordering Information

Model Number

Model Number	Description
PIBV2	Post Indicator/Butterfly valve supervisory switch
PIBV2A	Post Indicator/Butterfly valve supervisory switch (ULC model)

Part Number

Part Number	Description
A3010-00	Replacement hardware kit (wrenches, screw pack)
546-7000	Cover tamper switch kit
S07-66-XX	Tamper screws for cover
WFDW	Replacement tamper proof wrench for cover
HEXW	Replacement hex wrench

System Sensor Sales and Service

System Sensor Headquarters

3825 Ohio Avenue
St. Charles, IL 60174
Ph: 800/SENSOR2
Fx: 630/377-6495
Documents-on-Demand
800/736-7672 x3
www.systemsensor.com

System Sensor Canada

Ph: 905.812.0767
Fx: 905.812.0771

System Sensor Europe

Ph: 44.1403.276500
Fx: 44.1403.276501

System Sensor in China

Ph: 86.29.524.6253
Fx: 86.29.524.6259

System Sensor in Singapore

Ph: 65.6273.2230
Fx: 65.6273.2610

System Sensor – Far East

Ph: 85.22.191.9003
Fx: 85.22.736.6580

System Sensor – Australia

Ph: 613.54.281.142
Fx: 613.54.281.172

System Sensor – India

Ph: 91.124.637.1770 x.2700
Fx: 91.124.637.3118