

Product: Si6DB

Type: 6ltr cartridge operated AFFF extinguisher

Application: Hospitals, Supermarkets, Hotels, Restaurants, Paint shops, Fast Food chains, Clothing & Fabric industries, Industrial units, Offices etc.

Features:

- Slimline design
- Easy to handle
- Effective spray application
- Ergonomic design
- Replaces bulkier 9 lt. Water
- Higher performance

Benefits:

- Excellent fire ratings
- Uses 1% AFFF
- Reduced service time
- Reliability
- Knockdown performance
- Ideal for offices



TECHNICAL DATA

Model	Capacity	Type	Weight of charged extinguisher	Extinguishing agent	Volume of extinguishing agent	Working pressure	Discharge Times	Range of jet horizontal	Temperature range	Height mm	Width mm	Depth mm
Si6DB	6 litre	Cartridge	10.7kg	1% AFFF	6 litre	14 bar	>26 sec.	4-6m	-0°C to +60°C	610	270	160

FOAM EXTINGUISHERS are ideally suited where both class A & B fire risks exist. Aqueous Film Forming Foam or AFFF is particularly suited to fight liquid spill fires such as petrol, oil, fats, paints etc. and works by forming a film on the liquid to extinguish the fire. This extinguisher has also passed the electrical conductivity test at 35kv.



Model	A	B	C	D
S6DLWB	13 A	233 B		METAL

