

Product: S2LW

Type: 2ltr stored pressure AFFF portable fire extinguisher

Application: Ideal for: cars, vehicles, taxis, heavy goods vehicle cabs, kitchen, caravan, small boats, workshops etc.

Features:

- Compact design
- Patented safety strap
- All-purpose extinguisher
- Ergonomically designed
- Easy to use
- Handle design

Benefits:

- Very light weight
- Controlled discharge
- Completely refillable
- Supplied with pressure gauge
- Very cost-effective



TECHNICAL DATA

Model	Capacity	Type	Weight of charged extinguisher	Extinguishing agent	Volume of extinguishing agent	Working pressure	Discharge Times	Range of jet horizontal	Temperature range	Height mm	Width mm	Depth mm
S2LW	2lt	Stored pressure	3.5kg	AFFF	0.03lt	15 bar	20 sec.	>2m	0°C to +60°C	365	152	110

FOAM EXTINGUISHERS are ideally suited where both class A & B fire risks exist. Aqueous Film Forming Foam or AFFF is particularly suited to fight liquid spill fires such as petrol, oil, fats, paints etc. and works by forming a film on the liquid to extinguish the fire. This extinguisher has also passed the electrical conductivity test at 35kv.



Model	A	B	C	D
S2LW	5A	70B		METAL

