

Product: S6DLWB

Type: 6ltr stored pressure AFFF extinguisher

Application: Hospitals, Supermarkets, Hotels, Restaurants, Paint shops, Clothing & Fabric industries, Industrial units, Offices etc.

Features:

- Slimline design (Ø 170mm diam.)
- Easy to handle
- Effective spray application
- Ergonomic design
- Replaces bulkier 9 lt. Water
- Higher performance

Benefits:

- Uses 1% AFFF
- Reduced service time
- Reliability
- Knockdown performance
- Ideal for offices



TECHNICAL DATA

| Model | Capacity | Type | Weight of charged extinguisher | Extinguishing agent | Volume of extinguishing agent | Working pressure | Discharge Times | Range of jet horizontal | Temperature range | Height mm | Width mm | Depth mm |
|---------|----------|-----------------|--------------------------------|---------------------|-------------------------------|------------------|-----------------|-------------------------|-------------------|-----------|----------|----------|
| S6 DLWB | 6 litre | Stored pressure | 10.5kg | 1% AFFF | 6 litre | 7 bar | >36 sec. | 4-6m | -0°C to +60°C | 455 | 260 | 170 |

FOAM EXTINGUISHERS are ideally suited where both class A & B fire risks exist. Aqueous Film Forming Foam or AFFF is particularly suited to fight liquid spill fires such as petrol, oil, fats, paints etc. and works by forming a film on the liquid to extinguish the fire. This extinguisher has also passed the electrical conductivity test at 35kv.



| Model | A | B | C | D |
|--------|------|-------|---|---|
| S6DLWB | 13 A | 183 B | | |

