

Product: S9DLWB

Type: 9ltr stored pressure AFFF extinguisher

Application: Hospitals, Supermarkets, Hotels, and Restaurants, Paint shops, Fast

Food chains, Clothing & Fabric industries, Industrial units, Offices etc.

Features:

Good design

Easy to handle

• Effective spray application

• Ergonomic design

More effective than water

Higher performance

Benefits:

- Now available without torque
- Uses 1% AFFF
- Reduced service time
- Reliability
- Knockdown performance
- Ideal for offices

TECHNICAL DATA

S9 DLWB	9 litre	Stored	extinguis -her	agent	-hing agent 9 litre	7 bar	>53 sec.	horizontal 4-6m	range -0°C to +60°C	610	mm 260	200
Model	Capaci ty	туре	charged	Ü	extinguis	Working pressure	Discharge Times	Range of jet	ture	Height mm	Width mm	Depth mm

FOAM EXTINGUISHERS are ideally suited where both class A & B fire risks exist. Aqueous Film Forming Foam or AFFF is particularly suited to fight liquid spill fires such as petrol, oil, fats, paints etc. and works by forming a film on the liquid to extinguish the fire. This extinguisher has also passed the electrical conductivity test at 35kv.



Model	A	⊕ •	C M M	D METAL
S9DLWB	21 A	183 B		



Gloria UK Thame Park Road Thame Oxfordshire OX9 3RT 01844 265 133