

Product: W6DRC

Type: 6ltr high performance F Class extinguisher

Application: Portable fire extinguisher for use on **COOKING OIL**

Features:

- Lance applicator
- Effective spray application
- High performance Stored Pressure
- High quality epoxy resin paint finish
- 5 year guarantee
- Kitemarked to BSEN3:1996
- Manufactured to BS7937:2000
- CE marked under the P.E.D (Pressure Equipment Directive)

Benefits:

- Effective fire fighting performance
- Lance provides safe operating distance
- Minimum space required
- Rapid deployment
- Solution reacts with oil to prevent re-ignition
- Simple product training



TECHNICAL DATA

| Model | Capacity | Type | Weight of charged extinguisher | Extinguishing agent | Volume of extinguishing agent | Working pressure | Discharge Times | Range of jet horizontal | Temperature range | Height mm | Width mm | Depth mm |
|-------|----------|-----------------|--------------------------------|---------------------|-------------------------------|------------------|-----------------|-------------------------|-------------------|----------------|----------------|----------------|
| W6DRC | 6 litre | Stored Pressure | 11.8kg | RC 50 | 6 litre | 7 bar | >43 sec. | 4m | 0°C to +60°C | 533 (w/o hose) | 242 (w/o hose) | 180 (w/o hose) |

THESE EXTINGUISHERS are especially designed for tackling cooking oil / deep fat fryer (Class F) fires, but also have an effective capability for extinguishing Class A fires (wood, paper, straw, textiles, coal etc.). This extinguisher has also passed the electrical conductivity test at 35kv.



| Model | A | B | C | F |
|-------|------|---|---|-----|
| W6DRC | 13 A | | | 75F |

