


Dry Riser System (Inlets)

An inlet breeching at ground level provides the connection to the water supply. The system is normally dry and is charged by the fire brigade in an emergency. Breeching inlets have either 2 or 4 inlet connections complete with 2.5" male instantaneous inlets to BS336 fitted with non-return valves, 1" drain valve and caps and chains. A 100mm (4") rising main uses a 2-way inlet breeching in a vertical or horizontal position. A 150mm (6") rising main uses a 4-Way inlet breeching. Inlet Breechings comply with the requirements of BS 5041 Part 3.

The Breechings are normally housed in inlet cabinets, normally recessed into the external wall of the building in a vertical or horizontal position, 4-way breechings in a square inlet breeching cabinet, manufactured in accordance with BS 5041 Part 5. Cabinets for foam inlets are available on request.

Vertical Inlet Cabinets



Shield 1802	Red Ral 3002 As Standard
Shield 2020	Stainless Steel Satin Polished (See Cabinet Options)
Backbox Dimensions 595mm High x 395mm Wide x 295mm Deep	


(Minimum aperture 405mm wide 605mm high)

Cabinet Specifications:

Cabinet & Door: 16swg Zintec Steel.
Colour: As Standard Red Ral 3002.
Architrave: 30mm Wide All Round.
Glass: 6mm Georgian Wired, PRV Lettering.
Lock: Yale Slam Lock Keyed Alike.
Hinge: Stainless Steel Piano Hinge.
Conforms: To BS 5041 Part 5

The right is reserved to modify or withdraw any product without notice

Horizontal Inlet Cabinets



Shield 1799	Red Ral 3002 As Standard
Shield 2010	Stainless Steel Satin Polished (See Cabinet Options)
Backbox Dimensions 395mm High x 595mm Wide x 295mm Deep	

(Minimum aperture 605mm wide 405mm high)

Cabinet Specifications:


Cabinet & Door: 16swg Zintec Steel.
Colour: As Standard Red Ral 3002.
Architrave: 30mm Wide All Round.
Glass: 6mm Georgian Wired, PRV Lettering.
Lock: Yale Slam Lock Keyed Alike.
Hinge: Stainless Steel Piano Hinge.
Conforms: To BS 5041 Part 5

The right is reserved to modify or withdraw any product without notice

2-Way Inlet Breeching Valve



Shield 010	Outlet Flanged 100mm BS4504 PN16
Shield 071	Outlet Flanged 4" BS Table D
Shield 011	Outlet Screwed 4" BSPT



The right is reserved to modify or withdraw any product without notice



Fire Protection &
Flow Control Products

Tel: 01724 854199 Fax: 01724 854213

Email: sales@fireprotectioncentre.com

www.fpcdatacentre.co.uk

Freefax: 0800 65 200 31